

# HD ANALOG IR DOME CAMERA FIXED LENS

DI-350A36



<b>MODEL</b>	<b>DI-350A36</b>
Image Sensor	1/2.7" CMOS
Image Format	5MP - 4:3 / 4MP - 16:9
Effective Pixels	2592(H)×1944(V)
Scanning System	Progressive
Resolution	5MP: 2592x1944 @ 20FPS, 4MP: 2560x1440 @25/30FPS
Min. Illumination	0.01Lux (0 Lux with IR on)
Day & Night	True Day&Night (ICR)
IR LED	2 LED Array (20m)
OSD Menu	Available via CoC Only
CoC Support	Yes
Day & Night Mode	EXT, Color, B&W, Auto
Backlight Compensation	Off / BLC
S/N Ratio	≥35dB (AGC Off)
White Balance	ATW, Manual
Noise Reduce	2D-DNR
Video Output	5MP / 4MP (Selectable by OSD Menu) AHD/TVI/CVI (4MP Only)/ CVBS + PAL/NTSC (Selectable by DIP Switch on cable)
Defog	Not Available
Privacy Mask	Not Available
Motion Detection	Not Available
D-Effect	Mirror
Lens (Field of View)	3.6mm (74°)
Power	DC12V±10%, ~280mA
Operation Temp.	-30°C~+50°C
Waterproof	IP66
Dimension	104*82*93.2mm
Net weight	270g

## Main Features:

Sensor: 1/2.7", 5 Mega-Pixel

Selectable Output:

5MP: AHD / TVI

4MP: AHD / CVI / TVI

CVBS

PAL/NTSC

Lens: 3.6mm Mega-Pixel Fixed

True Day & Night – ICR

IR Range: 20m (2 Array LED)




IP66

CoC Support

Weight: 270g



Junction Box (PR-B37JB)  
is available



DIP Switch for Output Selection