

HDMI Accessories

3 to 1 HDMI Switcher

Model: PR-SW301(4K)

Allows the connection of 3 HDMI sources to a single HDMI display unit. After connection the required input can be chosen manually or selected by the device automatically.

- Compatible with HDMI 1.4a
- Support up to 4K@30Hz
- Deep color 12bit per channel
- "Smart switching" function that can detect live HDMI signal in different channels and switch to it automatically
- No power supply required for standard installation. If the HDMI output cable exceeds 5m – a CD5V power supply will be required (Not included)



AHD to HDMI/VGA/BNC Converter

Model: PR-AHD-Con

Converts AHD signal to HDMI/VGA/BNC signal for a connection of an AHD source to a standard display device.

- HDMI output compatible with HDCP, HDMI1.4
 - HDMI output resolutions: 720P@50/60Hz, 1080P@50/60Hz
 - VGA output resolutions: 800x600@60Hz, 1024x768@60Hz, 1366x768@60Hz, 1280x720@60Hz, 1920x1080@60Hz
 - Selectable output by physical button on the device
 - Supports both NTSC/PAL Video inputs –Automatic detection
 - Maximum output distance: HDMI: 20 meters, VGA: 5 meters, CVBS: 500 meters
- Note: Working Distance may be affected by the cable quality and length



HDMI Extender over Cat5e/Cat6

Transmits HDMI signal over Ethernet cable.

Model: PR-HDoNet+ / PR-HDoNet(IR)

- Working Distance: Up to 40m distance over cat5e cable. Up to 60m over Cat6 cable
- HDMI1.3 & 3D support
- 12Bit deep color and bandwidth of up to 225Mhz support
- Support video resolution of up to 1080P@60Hz
- Supported Audio formats: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD
- IR Signal transmission (PR-HDoNet(IR) Model only)
- DC5V power supplies included



Model: PR-HDoNet-E

- Working Distance: Up to 10m distance over cat5e cable. Up to 20m over Cat6 cable
- HDMI1.3 & 3D support
- Support video resolution of up to 1080P@60Hz
- Supported Audio formats: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD
- Passive Unit - No power required



HDMI USB KVM Extender over Cat5e/Cat6

Model: PR-HDKVMoNet

Transmits HDMI + USB + IR signals over Ethernet cable.

- Working distance: Up to 100m distance over cat5e cable. Up to 130m over Cat6 cable
- HDMI1.3 & 3D Support
- 12Bit deep color and bandwidth of up to 225Mhz support
- Support video resolution of up to 1080P@60Hz
- Supported Audio formats: DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
- Support USB2.0 Keyboard and mouse transmission
- Support IR signal transmission
- DC5V power supplies included

