

PoE Accessories

1 to 2 CH PoE Extender (Repeater)

Model: PoER-02

Split 1 Ch PoE to 2Ch and Extend PoE Signal additional 150 meter. Designed for Application where PoE camera or 2 located over 100 Meter Distance from the PoE Switch. Allows to transmit both cameras PoE signal Over 1 Ethernet . for Ease the installation, save on cabling cost and labor.



- Extends PoE Range Up To Additional 150 Meters
- 10/100Mbps Ethernet
- 2 Ch Output
- No Additional Power Supply Is Required
- Automatically Detects And Protects PoE Equipment From Being Damaged By Incorrect Installation
- Compliance With IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3af/at, Standards
- Wall Bracket/Earthling Terminal
- Rail (mail/female) Design to attached Several Unit In a Row



* Will cause a power lost of approx. 3 watt for its own operational use

* Power (Watt) which supplied to camera depend on: Number of cameras ,cable distance and Feeding PoE Port Power limitation! subject to Operational Spec.

Ethernet over Coax (EoC)

Model: EoC-01

Designed for applications where IP camera are replacing an old Analog cameras while the Coax cable and DC12V power infrastructure are already available.

- Set-Transmitter + Receiver
- Up To 150 Meter of Ethernet Over Coax
- Passive Units: No Power supply needed.
- Requires that the camera will be powered on



None PoE Power Over Ethernet Transmitter/Receiver

Model: DCoE-01

Design To Transmit DC Power and Ethernet Over Ethernet Cable.

- Set-Transmitter/Receiver
- 50 Meter Working Distance
- Required Camera External Power Supply
- Supply a DC Power Input To Camera And Not PoE

