


40M IR MOTORIZED VF BULLET CAMERA

I4-390IP5MVF



1/2.7" CMOS Sensor
2 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
Analytics Support

3.3-12mm Motorized Lens with Auto-Focus
40m IR Illumination
PoE Support
Local Storage
RS-485
I/O
2 Way Audio
Technician Port
IP 66 Protection
RS-485

Specifications (Based on v4.2.1)

| | | | |
|-------------------|-------------------|---|--|
| Camera | Video | Model | I4-390IP5MVF |
| | | Image Sensor | 1/2.7" CMOS (16:9) |
| | | Effective Pixels | 1920x1080 |
| | | Electronic Shutter | 1/25s ~ 1/100000s |
| | | Frame Rate | 1-25/30FPS |
| | Audio | Day & Night | ICR |
| | | Min. Illumination | Day: 0.022lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on |
| | Image Processing | Audio compression | G.711A/G.711U |
| | | Communication | Two-way Audio |
| | | Image Settings | AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable |
| Image Enhancement | | True WDR (120dB) / BLC / HLC / ROI | |
| Noise Reduction | | 3D-DNR | |
| Image Orientation | | Mirror/Flip | |
| Privacy Zone | | Yes | |
| Compression | Motion Detection | Yes | |
| | Analytics | Camera Tampering, Line Crossing, Sterile Area, Smart Search | |
| | Video Compression | H.265 / H.264 / MJPEG (Sub-Stream Only) | |
| | Resolution | 1080P (1920x1080), 720P (1280x720), D1, CIF | |
| | Multi-Stream | 11920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS) | |
| | Bit rate | 64Kbps ~ 4Mbps@H.265 / 128Kbps ~ 6Mbps@H.264 | |
| | Encode Mode | VBR/CBR | |
| | Image Quality | Five levels under VBR; Free adjustment under CBR | |

| | | |
|--------------|----------------------|---|
| Housing | IR Distance | 40m (48 IR LED) |
| | Lens (Field of View) | 3.3-12mm Motorized with Auto-Focus (109.8°-38.5°) |
| | Iris | Fixed Iris |
| | Lens Mount | Φ14 mount |
| | Protection Rate | Water Proof: IP66 |
| | Bracket | 3-Axis |
| Connectivity | Dimensions | Φ109mm×284mm |
| | Weight(gross) | 1115g |
| | Network | RJ45 (+PoE) |
| | Power | DC Socket |
| | Analog Video Output | CVBS(BNCx1) |
| | Audio Connectivity | 1Ch Input, 1Ch Output |
| | SD Card | Support Event recording over TF (128GB Max) |
| Network | RS485 | Yes |
| | Alarm | 1Ch Input, 1Ch Output |
| | Remote Monitoring | IE Browsing, CMS Software, Provision Cam2 Mobile App |
| | User Access | Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission |
| Others | Network Protocol | TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP |
| | ONVIF | Yes |
| | Ethernet | 100Mbps |
| Others | PoE | Yes |
| | Power Supply | DC12V/~600mA / PoE/~8.5W |
| | Work Environment | -30 C ~50 C, 10%~90% Humidity |

