



Network

BOX

## XNZ-L6320A

2MP H.265 32x Zoom Camera

FC |  | CE | EAC

### Key Features

- Maximum 2MP (1920 x 1080) resolution
- 4.44 ~ 142.6mm Optical 32x zoom, Digital 32x zoom
- Maximum 60fps@all resolutions (H.265 / H.264)
- H.265, H.264, MJPEG Codec, Multiple streaming
- Day & Night (ICR), WDR (120dB), Defog
- Video & Audio Analytics
- PoE, 12VDC, Micro SD/SDHC/SDXC 1slot 256GB

# XNZ-L6320A

2MP H.265 32x Zoom Camera



## Specifications

### Video

<b>Imaging Device</b>	1/2.8" 2MP CMOS
<b>Resolution</b>	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
<b>Max. Framerate</b>	H.265/H.264: Max. 60fps/50fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
<b>Min. Illumination</b>	Color: 0.05Lux (1/30sec, F1.6) B/W: 0.005Lux (1/30sec, F1.6)
<b>Video Out</b>	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation

### Lens

<b>Focal Length (Zoom Ratio)</b>	4.44 ~ 142.6mm (Optical 32X) (digital 32x, total 1024x zoom)
<b>Max. Aperture Ratio</b>	F1.6(Wide) ~ F4.4(Tele)
<b>Angular Field of View</b>	H: 64.66(Wide)~2.29(Tele) / V: 38.08(Wide)~1.30(Tele)
<b>Min. Object Distance</b>	Wide 1.5m(4.92ft) ,Tele 2m(6.56ft)
<b>Focus Control</b>	Auto, One shot AF
<b>Lens Type</b>	DC auto iris

### Operational

<b>Camera Title</b>	Displayed up to 85 characters
<b>Direction Indicator</b>	Support
<b>Day &amp; Night</b>	Auto(ICR)
<b>Backlight Compensation</b>	BLC, HLC, WDR, SSSDR
<b>Wide Dynamic Range</b>	120dB
<b>Digital Noise Reduction</b>	SSNR V
<b>Digital Image Stabilization</b>	Support
<b>Defog</b>	Support
<b>Motion Detection</b>	8ea, 8point polygonal zones
<b>Privacy Masking</b>	32ea, rectangular Support - Color: Grey/Green/Red/Blue/Black/White - Mosaic
<b>Gain Control</b>	OFF/ LOW/ MID/ HIGH
<b>White Balance</b>	ATW / AWC / Manual / Indoor / Outdoor / Mercury / Sodium
<b>Electronic Shutter Speed</b>	Minimum / Maximum / Anti flicker (2~1/12,000sec)
<b>Video Rotation</b>	Flip, Mirror
<b>Analytics</b>	Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification
<b>Serial Interface</b>	RS-485 (Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell)
<b>Alarm I/O</b>	Input 1ea / Output 1ea
<b>Alarm Triggers</b>	Analytics, Network disconnect, Alarm input
<b>Alarm Events</b>	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at Event Triggers Alarm output Handover(PTZ Preset)
<b>Audio In</b>	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm

<b>Audio Out</b>	Line out, Max.output level: 1Vrms
<b>Network</b>	
<b>Ethernet</b>	Metal shielded RJ-45(10/100BASE-T)
<b>Video Compression</b>	H.265/H.264: Main/Baseline/High, MJPEG
<b>Audio Compression</b>	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
<b>Smart Codec</b>	Manual(5ea area), WiseStream II
<b>Bitrate Control</b>	H.264/H.265: CBR or VBR MJPEG: VBR
<b>Streaming</b>	Unicast(20 users) / Multicast Multiple streaming(Up to 10 profiles)
<b>Protocol</b>	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP
<b>Security</b>	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Device certificate(Hanwha Techwin Root CA)
<b>Application Programming Interface</b>	ONVIF Profile S/G/T SUNAPI(HTTP API) Wisenet open platform

## General

<b>Webpage Language</b>	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
<b>Edge Storage</b>	Micro SD/SDHC/SDXC 1slot 256GB
<b>Memory</b>	1024MB RAM, 256MB Flash

## Environmental & Electrical

<b>Operating Temperature / Humidity</b>	-10°C ~ +55°C(-14°F ~ +131°F) / Less than 90% RH
<b>Storage Temperature / Humidity</b>	-50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH
<b>Input Voltage</b>	PoE(IEEE802.3af, Class3), 12VDC
<b>Power Consumption</b>	PoE: Max 7.5W, Typ 5.0W 12VDC: Max 5.7W, Typ 3.7W

## Mechanical

<b>Color / Material</b>	Black / Metal
<b>Product Dimensions / Weight</b>	72x63.9x135.4mm(2.83x2.52x5.33"), 480g(1.06 lb)

## DORI (EN62676-4 standard)

<b>Detect (25PPM/ 8PPF)</b>	Wide: 64.2m(199.1ft) / Tele: 1921.3m(6303.4ft)
<b>Observe (63PPM/ 19PPF)</b>	Wide: 24.3m(79.6ft) / Tele: 768.5m(2521.4ft)
<b>Recognize (125PPM/ 38PPF)</b>	Wide: 12.1m(39.8ft) / Tele: 384.3m(1260.7ft)
<b>Identify (250PPM/ 76PPF)</b>	Wide: 6.1m(19.9ft) / Tele: 192.1m(630.3ft)