

# 32 CH AHD DVR

## SA-32400AHD-2 (2U)\*



720P 1080P



\*The DVR can work in Either 32Ch Half Real-Time or 16Ch Real-Time. It cannot be mixed!

MODEL		SA-32400AHD-2 (2U) - Half Real-Time Mode	SA-32400AHD-2 (2U) - Real-Time Mode	
System	Compression Format	High profile H.264		
	ONVIF	No		
	Format	AHD / CVBS		
Video	Input	32CH AHD Standard BNC	16CH AHD Standard BNC	
	Standard Output	HDMI, VGA (800x600, 1024x768, 1280x1024)		
Audio	Input	16CH		
	Output	1CH		
	Two Way Audio	Yes		
Recording	AHD	Recording	32CH 1080P Half Real-Time	16CH 1080P Real-Time
		2MP (1080P)	480FPS (NTSC)/400FPS (PAL). Up to 15/12FPS	
		2MPL (1080P Lite)	No	
		1MP (720P)	960FPS (NTSC)/800FPS (PAL)	
	Analog	Recording	32CH 960H Real-Time	16CH 960H Real-Time
		960H	960FPS (NTSC)/800FPS (PAL)	
		D1	No	
		CIF	No	
	IP	Recording	No	
		3MP	No	
		2MP (1080P)	No	
		1.3MP (960P)	No	
		1MP (720P)	No	
	General	Recording Modes	Schedule, Manual, Motion, Sensor	
Playback	AHD/CVBS Playback	8CH	4CH	
	IP Playback	No		
	Search Mode	Time, Event, File Management		
Backup	USB	2 USB 2.0 Port		
	DVD Burner	Optional		
	Backup Format	AVI/DAT		
Remote Application	AHD Stream	Master & Sub-Stream: Up to 1-12/15FPS@1080P	Master & Sub-Stream: Up to 1-25/30FPS@1080P	
	Analog Stream	Master & Sub-Stream 1-25/30FPS@960H		
	IP Stream	Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1		
	Master Stream	Up to 4Ch@Recording Resolution		
	Browser	Supported		
	CMS	Yes		
	Mobile Application	Provision Cam2 for iOS/Android		
	User Access	10 Users Online with Professional Authority Management		
Alarm	Input	16CH		
	Output	4CH		
Storage	HDD	8 SATA (6TB Each)		
	E-SATA	1		
PTZ	Connection	RS-485 / CoC		
	Supported Protocols	Pelco D, Pelco P, Samsung, Visca, CoC		
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus		
Network	Ethernet	1000 Mbps (RJ-45)		
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P		
Others	Dimension	W430xD450xH89mm		
	IR Controller	Yes		
	Power Supply	AC110V/220V		
	Operation Temperature	0°C ~50°C		