

TCPA1B, TCPA2B, TCC8M, TCC800M, TCE800M

Wireless alarm peripherals

Honeywell’s family of wireless keyfobs gives your customers personalised control of their security system, the added convenience of controlling lights and appliances, and the security of knowing that emergency help will arrive with the press of a single or dual button.

From the entry-level TCE800M four-button keyfob to the advanced TCC800M bi-directional device that can provide system status on demand, the family of wireless remotes provides easy-to-use personal protection that your customers can take with them anywhere.

The TCPA1B and TCPA2B keyfobs are also supervised and fully waterproof for emergency help in all conditions and frequently used when a panic button is needed. The accessories available/provided with these models offer multi-wear possibilities for portable usage or fixing on walls or under tables.

The wireless keyfobs make Honeywell systems easy to operate and provide an extra level of convenience, comfort and peace of mind for your customers. Our wide range of wireless remote keyfobs provides the flexibility for any wireless application.

With more than 3 million peripheral devices installed over more than fifteen years in Europe, Honeywell’s Alpha/GY wireless range is the most reliable solution to complete alarm systems



FEATURES

- Rolling code encryption
- Radio range up to 500m in open area
- Two way
- European 868MHz frequency
- Compatibility with the Honeywell panel ranges: Domonial, Le Sucre, Galaxy Flex and Dimension, Galaxy G2⁽¹⁾ and Vista⁽²⁾
- Long-life lithium batteries
- LED indications for user feedback
- Icons for simple, easy-to-understand functionality⁽¹⁾

(1) Except TCPAxB






(2) Except TCE800M

COMPATIBILITY	TCPA1B	TCPA2B	TCE800M	TCC8M	TCC800M
Domonial		✓	✓		✓
Le Sucre™		✓	✓		✓
Galaxy Flex ⁽¹⁾	✓ ⁽⁵⁾	✓ ⁽³⁾	✓		✓
Galaxy Dimension ⁽¹⁾	✓ ⁽⁵⁾	✓ ⁽⁴⁾	✓		✓
Galaxy G2	-	✓ ⁽⁶⁾	✓		✓
Vista ⁽²⁾		✓	-		✓

Honeywell reserves the right to alter the specification of products without notice

(1) with C079-2 RF portal, (2) with 5882EUHS receiver, (3) since firmware V3.1.3, (4) since firmware V6.8.4, (5) with RF portal Firmware V3 onward, (6) with software V1.56 and above

Keyfobs range Wireless peripherals

					
CHARACTERISTICS	TCPA1B	TCPA2B	TCE800M	TCC8M	TCC800M
Buttons / LEDs	1 / 1	2 / 1	4 / 1	4 / 3	
Panic function (PA)		✓	✓	-	✓
Multi-action PA compatible	-	✓	-	-	
Setting / unsetting	-	Programmable	✓	✓	
Home automation	-	Programmable	✓	✓	
Arming status	-		-	✓	
Supervised device	✓		-	-	
Battery type	3V CR2032 x 1		3V CR2032 x 1	3V CR2032 x 1	
Dimensions (mm)	40 x 14,5		57 x 31,75 x 12,7	56 x 48 x 9	
Weight	14g		17g	19g	
Ingress Protection rate	IP67		IP32	IP32	
Color	Grey and white		Black	Black	
Operating Temperature	-10°C tot +55°C				
Storage Temperature	-20°C tot +70°C				
Humidity	5% tot 95%				
Regulations	EN50131 Grade 2, Class II NF&A2P	EN50131 Grade 2, Class II NF&A2P PD6662:2010/ BS8243:2010	EN50131 Grade 2, Class II NF&A2P	EN50131 Grade 2, Class II NF&A2P PD6662:2010	EN50131 Grade 2, Class II, NF&A2P
Accessories (supplied)	Belt clip/wall mount, Pendant, Keychain, Wristband		-	Blue and Silver ring sticker, Keyring	

ORDERING INFORMATION

TCPA1B	One button / one LED keyfob
TCPA2B	Two buttons / one LED keyfob
TCE800M	Four buttons / one LED keyfob
TCC8M	Four buttons / three LEDs keyfob (no dedicated panic function)
TCC800M	Four buttons / three LEDs keyfob

For additional information, please visit

www.honeywell.com/security/uk

Honeywell Security and Fire

Aston Fields Road
Whitehouse Industrial Estate
Runcorn
Cheshire
WA7 3DL
Tel: 08448 000 235
www.honeywell.com