

SD360


Wireless Smoke Detector



Features

| | |
|--------------------|--|
| | SD360 |
| Description | Wireless Ceiling-Mount Smoke Detector (Everday) |
| Features | <ul style="list-style-type: none"> ▶ High-sensitivity photoelectric smoke sensor ▶ Built-in siren ▶ Test / Hush button ▶ LED operation indicator |

Specifications

| | |
|----------------------------------|---|
| Detection Type | Photoelectric Chamber |
| Power | 3V lithium battery, Duracell or Panasonic CR123A (3 Vdc) |
| Battery Life | 3 years |
| RF Frequency | 433 or 868 MHz (868 MHz RF certification pending) |
| Alarm Level / Sensitivity | 1.38 to 2.36%/ft |
| Standby Current | 25 uA |
| Alarm Sound Level | 85 dB at 10 ft |
| Humidity | 10 ~ 85% |
| Operating Temperature | 0 to 49 °C (32 to 120 °F) |
| Dimensions | 12 cm diameter x 5 cm depth (4.7 x 0.2 in.) |
| Certification |  |





SD360

NEW Wireless Ceiling-Mounted Smoke Detector

Now available with ETL/ETLc




Intertek

* To comply with ETL / ETLc, SD360 must be installed with SP6000 or EVO192

* ETL / cETL is valid for 433MHz only

