

ATS1192

ATS Heavy-duty Smart Card Reader

Product Overview

The ATS1192 smart card reader connect directly on the RS485 data bus of the control panel or 4-Door Controller and may be configured and addressed via a LCD keypad. Some security options (Site code & 4-byte security code) are only programmable via TITAN and configuration cards. The ATS1192 is mainly used for outdoor applications and due to the waterproof construction it is suitable for use in harsh environments.

High quality cards & key fobs

Both the smart chip and antenna are embedded inside the cards & fobs. Printing is possible on the cards using any industry standard printer. The ATS1476 cards feature a programmable magnetic stripe for Time & Attendance or other applications.

Security Features

The ATS smart card technology has the ability to program a unique 268 million, 4-byte, combination security code (values from 0 through 127 are applicable for EMEA). This allows the memory card to unlock/open/disarm based on three keys; the card number, the Site code and the 4-byte security code. Once a 4-byte security code has been created, downloaded to the programmer and the cards, it is not possible to read the memory on the card or even recognise the card memory at any other reader or TITAN and programmer combination. Communications between TITAN and the programmer may also be password protected to prevent the 4-byte security code from being uploaded from the programmer into another PC running TITAN.

Read/Write Encryption

The ATS Smart card technology also features an exclusive read/write encryption. When a card is presented at a reader, data are downloaded into the reader, encrypted and re-written back into the card. The readers can also be configured to operate in stand-alone or connected to control devices like office equipment or vending machines. This function enables credits to be assigned on user cards and deducted by the readers, purely on a usage basis. Up to 65535 credits may be allocated in up to 4 different banks with 16 access levels and 4 locations. The reader determines of which bank credits have to be deducted and the number of credits per valid presentation.

Multiple Card Badging

The ATS1192 Heavy-duty smart card reader can be used for



Standard Features

- Full epoxy filled weather proof construction
- Heavy-duty version

ATS1192

ATS Heavy-duty Smart Card Reader

arming/disarming areas as well as for access applications in harsh environments. It is suitable for using the multiple card badging techniques which are available for the advisor MASTER control panel family. A user could arm the system in the evenings by badging his card three times within 10 seconds interval. Another application could be for doors which can be programmed so that badging once unlocks, badging twice with the same card keeps the door unlocked to allow people in and out without card, and badging three times re-locks the door.

Specifications

Supply voltage	9 - 14 V
Current consumption	25 - 80 mA
Open collector output	1(25 mA max)
"Request to exit" input	Yes
Max. distance from panel	1.5 km
Max. number per panel bus	16
Specified cable	Aritech WCAT 52/54 or equivalent
Data bus monitoring	Continuously monitored for offline condition of all devices on data bus
Addressing	Via keypad, TITAN or config. card
IP rating	IP54
Dimensions (W x H x D)	42 x 150 x 16 mm
Operating temperature	-35 to +66°C
Colour	Dark grey
Programmable OC output	pulse from 1 msec to 2.5 secs time from 1 sec to 193 days latch
Connectivity	RS485 data bus device or standard Wiegand for connection on the 4 reader inputs of the ATS1250
Read range (cm)	6 - 10
Optical pry-off tamper sensor	Yes
Epoxy-filled weatherproof construction	Yes
Red & Blue LEDs	Configurable as nightlight, lock status or alarm area status

Ordering Information

Part No.	Description
ATS1192	ATS Heavy-duty Smart Card Reader
ATS1471	ATS keyfob
ATS1475	ATS proximity card, packed by 10 pcs.
ATS1476	ATS proximity card, with Magstripe,
ATS1477	ATS fibertag.