

P A R K I N G

EXIT ONLY

ENTER



OVS-01CC

Vehicle counting sensor

The OVS-01CC from OPTEX is designed to reliably detect and count moving vehicles up to 60km/h. It also eliminates the hassle associated with the installation of a ground loop. No more concrete cutting required. The OVS-01CC can be mounted at 500mm from the ground and can detect both small and large vehicles.



OVS-01CC

Vehicle counting sensor

Moving vehicle counting


The OVS-01CC is designed to count moving vehicles up to 60km/h. It is installed above ground and can be mounted on a pole or post. Its detection area can be customised with 8 range settings, 5 sensitivity settings and one-touch calibration.



Easier and more cost-effective installation

With the OVS-01CC there is no need to stop traffic or engage in engineering work during installation. The vehicle counter can be mounted quickly and easily on a pole or on the wall; the calibration is done easily. No additional loop detector is required.

Adjustable microwave patterns



Microwave detection patterns (blue above) are adjustable from 1m to 8m. The OVS-01CC also features 5 sensitivity settings.

OVS-01CC Specifications

Detection method	Microwave (Doppler shift and FMCW)	
Frequency	24GHz	
Response time	300msec	
Power supply	12-24VDC	
Current consumption	Max 190mA (at 24VDC) with Heater ON Max 70mA (at 24VDC) when Heater is OFF	
Output	Relay output DC30V, 0.3A (NO/NC switchable)	
Input	NO/NC input	
Detection range	1m to 8m programmable maximum range	
Detectable vehicle speed	2 to 60km/h (1.24mph-37.28mph)	
Parameters	Sensitivity	Level 1 to 5
	Outputs	2 x (N.O. / N.C) Contacts
	Max. Range	1m, 2m, 3m, 4m, 5m, 6m, 7m, 8m.
Indicator	Normal operation	Stand-by: Solid Green, Detection: Solid Red, Unsuitable environmental notification: Slow Blinking Green
	Detection area check	Non detection: Blinking Green Detected: Blinking Red
	Calibration	Getting ready: Slow Blinking Blue, Calibrating: Quick Blinking Blue
Sensor reset	Reset completed: Blinking yellow for 2 seconds	
Operation temperature	-30°C to 50°C (-22°F to 122°F)	
Operation humidity	95% max. (non-condensing)	
International Protection code	IP65	
Installed condition	Indoor/Outdoor	
Installation height	Installation Height of 500mm. (19.69in.)	
Horizontal angle adjustment	Horizontally: +/-30 deg. (5 deg. steps)	
Weight	480g (Including accessories)	
Accessories	4 screws and installation manual	



OPTeX (EUROPE) LIMITED

EMEA Headquarters
T: +44 (0)1628 631 000
Dubai branch
T: +971 (0)4 501 53 94
E: marketing@optex-europe.com
www.optex-europe.com

OPTeX Security SAS

(France and North Africa)
OPTeX Security SAS
T: +33 (0)4 37 55 50 50
E: contact@optex-security.com
www.optex-security.com

OPTeX Security Sp. z o.o.

(Eastern Europe,
CIS countries, Turkey)
Optex Security Sp. z o.o.
T: +48 (22) 598 06 60
E: optex@optex.com.pl
www.optex.com.pl

OPTeX Technologies BV

(Benelux)
OPTeX Technologies B.V.
T: +31 70 4194100
E: info@optex.eu
www.optex.eu