

## **Features**

- Approved to AS ISO 7240 Parts 3, 5, & 25
- ▶ RED compliant
- ▶ Optical Combined Sounder
- ▶ Incorporated Internal algorithm processing for optimal performance
- ▶ Tamper switch
- ▶ Up to 10 years battery life\*
- ► Utilises standard low cost lithium battery technology
- ▶ Bi-directional wireless communications
- ► Self optimising wireless amplitude and frequency
- Compatible with all Ekho Translator/Expander modules.



## **Description**

The EK-WL8-HS/AU is a wireless A1R heat sensor that Incorporates a internal sounder. It is a fully intelligent device and compatible with the Ekho wireless Translator and Expander modules.

The sensor is designed for installations where smoke detection technology is not suitable.

Utilising well-proven adaptive radio signal processing algorithms ensure the highest levels of life safety and system reliability are achieved. An inbuilt magnet test allows easy activation to verify correct functionality and response.

Specifications		
Ordering code	EK-WL8-HS/AU	
Operating frequency range	918 - 926 MHz	
Communication range (in open air)	1200 m	
Modulation type	GFSK	
Operating frequency channels	6	
Max. radiated power	≤ 25 mW	
Sound pressure level @ 1m	>96 dB(A) for all modes	
Frequency range	500 - 3500 Hz	
IP Rating	43	
Operating temperature range	- 10 °C to + 55 °C	
Max. tolerated humidity	95% RH (non-condensing)	
Weight (g) / Dimensions (mm)	200 / Ø 111 x H 65	
Power supply (Dual 3V lithium batteries)	1 x Primary cell (CR123A)	1 x Secondary cell (CR123A)
	1.2 Ahr	1.2 Ahr
	8 - 10 years primary battery life*	8 months secondary battery life

## **Standards & Approvals**

AS ISO 7240-3: Sounders

AS ISO 7240-25: Components using radio links

AS ISO 7240-5 Thermal Detectors





















